

# HOOVER TREATED WOOD PRODUCTS, INC.

## ***TECHNICAL NOTE***

FOR ADDITIONAL INFORMATION: [www.frtw.com](http://www.frtw.com) or 1-800-TEC-WOOD (832-9663)  
FOR SALES INFORMATION 1-800-531-5558 or 706-595-1264

### **FASTENER and HARDWARE INFORMATION** ***MICRO-GUARD*<sup>®</sup>** **Preservative Treated Wood**

For interior or exterior conditions, use fasteners and hardware that comply with appropriate building code requirements and manufacturer's recommendations. As with any good design and construction practice *MICRO-GUARD*<sup>®</sup> treated wood should not be used in applications where trapped moisture or water can occur.

For exterior applications, the following minimum galvanization levels may be used for connectors, joist hangers, fasteners and other hardware that are placed in direct contact with exterior applications of *MICRO-GUARD*<sup>®</sup> treated wood.

Fasteners, nails and screws should conform to ASTM-A153 (1 oz/ft<sup>2</sup>).

Hardware, such as connectors, joist hangers, etc. shall conform to ASTM – A653 G90 (0.90 oz/ft<sup>2</sup>).

Stainless Steel (Type 304 and 316) fasteners are required for Permanent Wood Foundations below grade and are recommended for use with treated wood in other severe exterior applications such as swimming pools, salt water exposure and other critical environments. Where design and or actual conditions allow for constant, repetitive or long periods of wet conditions that favor corrosion, only stainless steel fasteners should be used.

Aluminum fasteners and other building products, such as flashing, siding, roofing, gutters, door and window trim, nails, fasteners and other hardware, may be placed in direct contact with *MICRO-GUARD*<sup>®</sup> when used for code compliant interior or above ground applications, such as decks, or fencing. Applications must provide proper water drainage and not allow the wood to be exposed to standing water or to water immersion. Manufacturers of aluminum products or who use aluminum products may have specific recommendations regarding compatibility of their products.

Fasteners used with *MICRO-GUARD*<sup>®</sup> must be in accordance with Section 2304.9.5 of the IBC and Section R319.3 of the IRC, except that aluminum fasteners are permitted.

The effects of other building materials within a given assembly, along with environmental factors, should also be considered when selecting the appropriate hardware and fasteners for projects containing treated wood.

*MICRO-GUARD*<sup>®</sup> is a registered trademark of Hoover Treated Wood Products Inc.

DISCLAIMER OF LIABILITY FOR RELIANCE ON INFORMATION PROVIDED BY HOOVER TREATED WOOD PRODUCTS, INC.:  
The information contained herein is true and accurate to the best of our knowledge, but is provided without warranty or guarantee. Since the conditions of use are beyond our control, Hoover Treated Wood Products, Inc. ("Hoover") disclaims all liability and assumes no legal responsibility for damages resulting from use of or reliance upon the information contained herein